

# SBTL6000

## Swing Barrier with Modular Design



RFID



Fingerprint



QR code




Palm  
verification




Visible light  
facial recognition



SBTL6000 is a swing barrier with a modular design that realizes fast switching between different readers. And reader installation can be completed by merely pull-out and plug-in. After installing the corresponding readers, SBTL6000 can support multiple verification methods, including RFID, fingerprint, QR code, palm verification and visible light facial recognition. Especially, palm verification and visible light facial recognition can realize touchless entrance control that avoids hands exposing to bacteria and boost public hygienic security.



RFID



Fingerprint



QR code



Palm verification



Visible light facial recognition

Modular design readers are also suitable for FBL6000 Pro series.



## Specifications

Power Requirements	AC 100 ~ 120V / 200 ~ 240V, 50 / 60Hz
Operating Temperature	-10°C ~ 55°C
Operating Humidity	20% ~ 95% (non-condensing)
Operating Environment	Indoor / Outdoor (if sheltered)
Lane Width (mm)	635
Infrared Sensor	6 pairs
Dimension(L*W*H)	1400 * 180 * 1000 (mm)
Dimension with Packing(L*W*H)	1580 * 340 * 1270 (mm) (2pcs)
Weight with Packing(kg)	150
LED Indicator	Support
Cabinet Material	SUS304 Stainless Steel
Lid Material	SUS304 Stainless Steel + Acrylic
Barrier Material	Tempered Glass
Barrier Movement	Swing
Emergency Mode	Support

## Dimensions (mm)

